Tele: +886-3-4644666 Fax: +886-3-4644578 E-mail: thermtec@ms45.hinet.net

WWW.thermotech.com.tw

IN-Fluo 鐵氟龍塗佈玻纖布系列

基材: KM600 系耐高溫布

表面: PTFE (鐵氟龍)COATING

耐潟: 287℃


特性: 抗化學品, 具彈性及氣密性,

耐油水,耐候,防沾黏,

潔淨表面,防火

應用範圍: 膨脹接頭,防震接頭,保溫夾克,

伸縮蛇管,無塵室保溫





IN-Fluo PTFE/Fiberglass Cloth

This series of PTFE coated/impregnated fiberglass fabric are designed for use in removable blankets as weather/chemical resistant barrier. This economic grade fabric is easily sewn and is flexible enough to conform to intricate shapes. The PTFE coating is extremely resistant to most industrial chemicals and has been in applications to 287°C.

Advatnages:

- Flame Resistant,
- Excellent chemical, oil, and weather resistant,
- Suitable for clean room applications

Data and Availability

Data and Attailability				
產品	厚度	單位面積重	張力強度	每捲呎吋
Product ID	Thickness	Areal Weight	Tensile Strength	Roll sizes (m)
	(mm)	(g/m^2)	(N/50mm)	
2-23P/P	0.18	230	1600X1350	$1.0x50^{+}$
2-24F/F	0.21	237	657X657	1.5X45.7
2-27F/F	0.21	271	482X482	1.5X45.7
3-43P/P	0.3	425	2670x2220	1.5x45.7
4-56P/P	0.36	560	3500x2600	1.5x45.7
4-61P/P	0.38	610	3500x2600	1.5x45.7
6-78P/P	0.6	780	3660x3170	1.5x45.7
9-115P/P	0.86	1153	5400×4600	1.5x45.7

Your solution for Thermal Insulation since 1989?

Thermotech cannot predict all of the potential applications for which customers may attempt to use our products. Our products will have varying degrees of effectiveness for each potential application depending on application conditions and the length of use. If the customer has any questions regarding the use of our products in a particular application, please contact Thermotech and we will provide a sample for testing.

The above technical data are subject to change w/o prior notice and are not intended to be used as specifications.